

Serial No.: 10/089,802

IN THE CLAIMS:

1. (Currently Amended) A method of driving a display panel, comprising:

setting a pixel luminance value to a target luminance setting value at least two times;

carrying out luminance value setting operations such that a luminance setting value is set ~~two or more times~~ and to a different luminance setting value each time a luminance value setting operation is preformed, so that the ~~set~~ luminance setting value is changed with the ~~elapsing~~ elapse of driving time.

2. (Currently Amended) The method of driving a display panel according to claim 1, wherein the luminance setting values are determined from measured luminance information, and said pixel luminance value is corrected ~~so as to match with the~~ determined luminance setting values.

Serial No.: 10/089,802

3. (Currently Amended) A method of driving a display panel wherein pixels are driven, luminance information is captured from the pixels and measured, correction values are calculated from the measured luminance information and a luminance setting value, the correction values are stored in the a correction memory, and a driving amount is corrected in accordance with the correction memory, the method comprising:

setting pixel luminance value to a target luminance setting value at least two times;

carrying out luminance setting operations such that a luminance setting value is set ~~two or more times and to a different luminance setting value each time~~ a luminance setting value operation is performed, so that the ~~set-luminance setting value~~ is changed with the elapsing-elapse of driving time.

4. (Original) The method of driving a display panel according to claim 1, wherein each of the luminance setting values does not exceed a preceding luminance setting value.

Serial No.: 10/089,802

5. (Currently Amended) A method of driving a display panel, comprising:

setting a pixel luminance value to a target luminance
setting value at least two times at predetermined time
intervals;

carrying out luminance correcting operations such that ~~luminance is corrected two or more times at predetermined intervals and each of the~~ time intervals between the luminance correction operations differ, whereby the starting interval of recorrection operation is varied.

6. (Original) The method of driving a display panel according to claim 5, wherein the intervals between the luminance correction operations are varied according to the luminance degradation characteristics of display elements.

7. (Currently Amended) A method of driving a display panel wherein pixels are driven, luminance information is captured from the pixels and measured, correction values are calculated from the measured luminance information and a

Serial No.: 10/089,802

luminance setting value, the correction values are stored in the a correction memory, and a driving amount is corrected in accordance with the correction memory, the method comprising:

carrying out a series of renewal operations on the correction memory for all of the pixels at specified time intervals.

8. (Currently Amended) The method of driving a display panel according to claim 7, wherein the series of renewal operations on the correction memory, instead of being carried out at specified time intervals, is repeated continuously.

9. (Currently Amended) The method of driving a display panel according to claim 2, wherein the operations for correcting luminance setting values are carried out during periods other than video output periods.

Serial No.: 10/089,802

10. (Currently Amended) The method of driving a display panel according to claim 3, wherein ~~the operations for capturing~~ luminance information from the pixels comprise at least illuminating the pixels during periods other than video output periods.

11. (Original) The method of driving a display panel according to claim 10, wherein the periods other than video output periods are vertical blanking periods, and luminance information from a given number of grouped pixels is captured during each of these periods.

12. (Original) The method of driving a display panel according to claim 10, wherein adjacent pixels are not successively driven.

13. (Original) The method of driving a display panel according to claim 3, wherein the correction value calculations are carried out using both measured luminance information and degradation characteristics related to either the luminance of

Serial No.: 10/089,802

elements for which luminance has been measured or to the luminance of pixels for which luminance has been measured.

14. (Currently Amended) The method of driving a display panel according to claim 13, wherein the display panel has a light-emitting surface with phosphors, and ~~instead of degradation characteristics related to either the luminance of the elements or the luminance of the pixels, the correction value calculations are carried out using both measured luminance information and degradation characteristics related to the luminance of the phosphors are used.~~

15. (Original) The method of driving a display panel according to claim 13, wherein the degradation characteristics are measured in advance, rates of degradation are calculated based on the driving integral amount of every pixel, correction values are calculated using both the measured luminance information and the rates of degradation, and the correction memory is renewed.

Serial No.: 10/089,802

16. (Original) The method of driving a display panel according to claim 2, wherein until the difference between the measured luminance information and the luminance setting value reaches a fixed value or less, correction operations are repeated continuously.

17. (Original) The method of driving a display panel according to claim 3, wherein the captured luminance information is driving current.

18. (Original) The method of driving a display panel according to claim 3, wherein the captured luminance information is that of the starting point of the illumination of pixels.

19. (Original) The method of driving a display panel according to claim 3, wherein the display panel has at least an anode electrode and a light-emitting surface having a plurality of phosphors on the anode electrode, and the captured luminance information is anode current.

Serial No.: 10/089,802

20. (Currently Amended) A method of driving a display panel, comprising, in an initial stage after fabrication of the panel, illuminating all of pixels in the panel one at a time, capturing luminance information from the pixels, and setting pixel luminance to a target luminance setting value at least two times; two or more times and
carrying out luminance setting operations such that a luminance setting value is set to a different luminance setting value each time, calculating correction values from the captured luminance information and the luminance setting value, and storing the correction values in a correction value memory as initial correction values.

21. (Original) The method of driving a display panel according to claim 3, wherein input luminance signals are corrected in accordance with the correction values stored in the correction memory.

Serial No.: 10/089,802

22. (Original) The method of driving a display panel according to claim 3, wherein the amplitude value or the pulse width of driving signals applied to the display panel is corrected in accordance with the correction values stored in the correction memory.

23. (Original) The method of driving a display panel according to claim 3, wherein the correction values are calculated so as to incorporate data for γ correction for each pixel and stored to the correction memory.

24. (Currently Amended) The method of driving a display panel according to claim 3, wherein a gray scale realization method for the display panel is either an amplitude control method or pulse width control method.

25. (Currently Amended) The method of driving a display panel according to claim 3, wherein a gray scale realization method for the display panel is a gray scale system of ~~gray~~ ~~scale~~ such that except when an output is completed, a current or

Serial No.: 10/089,802

voltage value for amplitude control is changed only in the an
increasing direction of increase.

26. (Currently Amended) The method of driving a display panel according to claim 3, wherein a gray scale realization method for the display panel is a driving system ~~of driving~~ such that amplitude control and pulse width control are carried out simultaneously.

27. (Original) The method of driving a display panel according to claim 26, wherein for the gray scale control, the amplitude control is such that using m high-order bits of gray scale data represented by n bits, where m and n are arbitrary integers, a current or voltage value controlled by amplitude is outputted at intervals of $1/2^m$ maximum value and the pulse width control is such that using $(n-m)$ low-order bits, pulse width is controlled at intervals of $1/2^{(n-m)}$ maximum value.

Serial No.: 10/089,802

28. (Original) The method of driving a display panel according to claim 26, wherein the LSB of current or voltage value output is outputted twice, or the LSB or output pulse width is outputted twice, or the LSB of both are outputted twice.

29. (Original) The method of driving a display panel according to claim 26, wherein the number of divisions of output for pulse width control is greater than the number of divisions of output for amplitude control.

30. (Currently Amended) The method of driving a display panel according to claim 3, wherein a gray scale realization method of the display panel is a driving method for realizing gray scale display comprising switching between amplitude control or pulse width control and a system of gray scale control in which amplitude control and pulse width control are carried out simultaneously.

Serial No.: 10/089,802

31. (Currently Amended) The method of driving a display panel according to claim 30, wherein, when the luminance signal level to be outputted is equal to or less than a reference value, amplitude control or pulse width control is carried out, and when equal to or greater than a reference value, the system of gray scale control where amplitude control and pulse width control are carried out simultaneously is carried out to realize gray scale display.

32. (Original) The method of driving a display panel according to claim 31, wherein the reference value is a number of output gray scale levels and is set to be the number of gray scale levels on the pulse width control side in the system of gray scale control where amplitude control and pulse width control are carried out simultaneously.

33. (Currently Amended) The method of driving a display panel according to claim 30, wherein the gray scale realization system is switched according to time to realize gray scale display.

Serial No.: 10/089,802

34. (Currently Amended) A luminance correction device, comprising means for setting pixel luminance to a target luminance setting value at least two times, and luminance resetting means for carrying out luminance setting operations such that a luminance setting value is set two or more times and to a different luminance setting value each time, and wherein the set-luminance setting value is changed with the elapsing elapse of driving time.

35. (Currently Amended) The luminance correction device according to claim 34, further comprising luminance correcting means for correcting pixel luminance so as to match with the luminance setting value and means for determining the luminance setting value from measured luminance information.

36. (Currently Amended) A luminance correction device for a display panel, ~~comprising~~ comprising:
means for setting pixel luminance to a target luminance setting value at least two times;

Serial No.: 10/089,802

_____luminance resetting means for carrying out luminance setting operations such that a luminance setting value is set ~~two or more times and to~~ a different luminance setting value each ~~time,~~ time;

_____driving means for driving ~~pixels,~~ pixels;

_____luminance measuring means for capturing luminance information from the ~~pixels,~~ pixels;

_____a correction memory for storing correction ~~values,~~ values;

_____calculating means for calculating correction values from the measured luminance information and the luminance setting value and storing the correction values to the correction memory, and correcting means for correcting a driving amount in accordance with the correction memory.

37. (Original) The luminance correction device according to claim 34, wherein each of the luminance setting values does not exceed a preceding luminance setting value.

Serial No.: 10/089,802

38. (Currently Amended) A luminance correction device, comprising means for setting pixel luminance to a target luminance setting value at least two times at predetermined intervals, and luminance correcting means for carrying out luminance correcting operations such that ~~luminance is corrected two or more times at predetermined intervals and each of the~~ time intervals between the luminance correction operations differ, and wherein the starting interval of recorrection operation is varied.

39. (Original) A luminance correction device according to claim 38, wherein the intervals between the luminance correction operations are varied according to luminance degradation characteristics of display elements.

40. (Currently Amended) A luminance correction device for a display panel, comprising driving means for driving pixels, luminance measuring means for ~~capturing~~ measuring luminance information from the pixels, a correction memory for storing correction values, calculating means for calculating correction

Serial No.: 10/089,802

values from measured luminance information and the luminance setting value and storing the correction values to the correction memory, correcting means for correcting a driving amount in accordance with the correction memory, and controlling means for carrying out a series of renewal operations on the correction memory for all of the pixels at specified intervals.

41. (Currently Amended) The luminance correction device for a display panel according to claim 40, wherein the controlling means is such that the series of renewal operations on the correction memory, instead of being carried out at specified time intervals, is repeated continuously.

42. (Currently Amended) The luminance correction device according to claim 35, wherein the operations for correcting luminance setting values are carried out during periods other than video output periods.

Serial No.: 10/089,802

43. (Currently Amended) The luminance correction device for a display panel according to claim 40, further comprising controlling means for controlling the ~~operations for capturing~~ capture of luminance information from the pixels so that at least the pixels are illuminated during periods other than video output periods.

44. (Original) The luminance correction device for a display panel according to claim 43, wherein the periods other than video output periods are vertical blanking periods, and luminance information from a given number of grouped pixels is captured during each of these periods.

45. (Original) The luminance correction device for a display panel according to claim 43, wherein the controlling means is such that adjacent pixels are not successively illuminated.

Serial No.: 10/089,802

46. (Currently Amended) The luminance correction device for a display panel according to claim 36, ~~comprising, instead of the~~ wherein said calculating means, ~~calculation correcting~~ means for calculating correction values ~~using~~ uses both the measured luminance information and degradation characteristics related to either the luminance of elements for which luminance has been measured or to the luminance of pixels for which luminance has been measured and for renewing a correction memory.

47. (Currently Amended) The luminance correction device for a display panel according to claim 46, wherein the display panel has a light-emitting surface of phosphors, and wherein the calculation correcting means is such that, ~~instead of the degradation characteristics related to either the luminance of the elements or the pixels,~~ the correction value calculations are carried out using both the measured luminance information and degradation characteristics related to the luminance of the phosphors ~~is used~~.

Serial No.: 10/089,802

48. (Original) The luminance correction device for a display panel according to claim 46, wherein the calculation correcting means is such that the degradation characteristics are measured in advance, rates of degradation are calculated based on the rates on the driving integral of driving current for every pixel, correction values are calculated using both the measured luminance information and the rates of degradation, and the correction memory is renewed.

49. (Original) The luminance correction device for a display panel according to claim 35, further comprising controlling means for controlling the correction operations so that until the difference between the measured luminance information and the luminance setting value reaches a fixed value or less, the correction operations are repeated continuously.

Serial No.: 10/089,802

50. (Original) The luminance correction device for a display panel according to claim 36, wherein the luminance measuring means is such that the captured luminance information is driving current.

51. (Original) The luminance correction device for a display panel according to claim 36, wherein the luminance measuring means is such that the capturing luminance information is that of the starting point of the illumination of pixels.

52. (Original) The luminance correction device for a display panel of claim 36, wherein the display panel has at least an anode electrode and a light-emitting surface having a plurality of phosphors on the anode electrode, and the captured luminance information is anode current.

53. (Currently Amended) The luminance correction device for a display panel, comprising:

means for setting pixel luminance to a target luminance setting value at least two times;

Serial No.: 10/089,802

luminance resetting means for carrying out luminance setting operations such that a luminance setting value is set ~~two or more times and to~~ a different luminance setting value each time: and

controlling means for, in the initial stage after fabrication of the panel, illuminating all of the pixels in the panel one at a time, capturing luminance information from the pixels, calculating correction values from the luminance information and a luminance setting value, and storing the correction values to a correction memory as initial correction values.

54. (Currently Amended) The luminance correction device for a display panel according to claim 36, wherein the correcting means for correcting a driving amount in accordance with correction values stored in a correction memory ~~corrects is~~ for correcting input luminance signals.

Serial No.: 10/089,802

55. (Currently Amended) The luminance correction device for a display panel according to claim 36, wherein the correcting means for correcting a driving amount in accordance with correction values stored in a correction memory ~~corrects~~ is for correcting the amplitude or the pulse width of driving signals applied to the display panel in accordance with the correction values stored in the correction memory.

56. (Currently Amended) A driving device for a display panel, the device comprising the luminance correction device for a display panel according to claim 36, and wherein a gray scale realization method for the display panel is an amplitude control method or pulse width control method.

57. (Currently Amended) A driving device for a display panel, the device comprising the luminance correction device for a display panel according to claim 36, and wherein a gray scale realization method for the display panel is a system of gray scale display such that except when an output is completed, a

Serial No.: 10/089,802

current or voltage value for amplitude control is changed only in the direction of increase.

58. (Currently Amended) A gray scale driving device for a display panel, the device comprising the luminance correction device for a display panel according to claim 36, and wherein a gray scale realization method of the display panel is a driving system of driving such that amplitude control and pulse width control are carried out simultaneously.

59. (Original) The driving device for a display panel according to claim 58, wherein for the gray scale control, the amplitude control is such that using m high-order bits of gray scale data represented by n bits, where m and n are arbitrary integers, a current or voltage value controlled by amplitude is outputted at intervals of $1/2^m$ maximum value and the pulse width control is such that using $(n-m)$ low-order bits, pulse width is controlled at intervals of $1/2^{(n-m)}$ maximum value.

Serial No.: 10/089,802

60. (Original) The driving device for a display panel according to claim 58, wherein the LSB of current or voltage value output is outputted twice, or the LSB or output pulse width is outputted twice, or the LSB of both are outputted twice.

61. (Original) The driving device for a display panel according to claim 58, wherein the number of divisions of output for pulse width control is greater than the number of divisions of output for amplitude control.

62. (Currently Amended) A driving device for a display panel, comprising a luminance correction device for a display panel of claim 36, and wherein a gray scale realization method of the display panel is a driving method for realizing gray scale display comprising switching between amplitude control or pulse width control and a system of gray scale control in which amplitude control and pulse width control are carried out simultaneously.

Serial No.: 10/089,802

63. (Original) The driving device for a display panel according to claim 62, further comprising means for realizing gray scale by, when the luminance signal level to be outputted is equal to or less than a reference value, carrying out amplitude control or pulse width control, and when equal to or greater than a reference value, carrying out the system of gray scale control where amplitude control and pulse width control are carried out simultaneously.

64. (Original) The driving device for a display panel according to claim 63, wherein the reference value is a number of output gray scale levels and is set to be the number of gray scale levels on the pulse width control side in the system of gray scale control where amplitude control and pulse width control are carried out simultaneously.

65. (Original) The driving device for a display panel according to claim 62, further comprising a means for realizing gray scale by switching the gray scale realization system according to time.

Serial No.: 10/089,802

66. (Original) The driving device for a display panel according to claim 56, wherein a correction memory has, for each pixel, a number of values equal to the number of levels of amplitude value.

67. (Original) The driving device for a display panel according to claim 56, wherein the correction memory has, for each pixel, values that incorporate data for γ correction.

68. (Original) A driving device for a display panel, the device comprising the luminance correction device according to claim 36, and wherein at least two of the correction memory, the correcting means, the calculating means, and the controlling means are combined.

69. (Original) An image display device comprising the luminance correction device according to claim 36.

Serial No.: 10/089,802

70. (Original) A light source comprising the luminance correction device according to claim 36.